

# DALAPRO<sup>®</sup>

# HYDRO

Ready-mixed, Ecolabelled hand filler for use in wet rooms.



Blue tinted hand filler specially developed for wet rooms.

Provides a hard and water-repellent surface and premium surface finish for further treatment.

For plaster and concrete surfaces indoors.

Good filling capacity.

Easy to sand, use 180-220 grit paper.

Special formulation for embedding papertape and cornerbeads.

Nordic Ecolabelled.

## DALAPRO<sup>®</sup> HYDRO

**Ready-mixed Ecolabelled hand filler for use in wet rooms.**

### PRODUCT INFORMATION

Dalapro Hydro is a ready-mixed hand filler for use in wet rooms or where an extra durable surface is desired. A high binder content in the filler gives the product a hard, water repellent surface, and maximum adhesion to the substrate. The product is suitable for joint filling and thin smoothing. Suitable for most substrates in new construction and renovation. Blue color. Nordic Eco-labelled.

### USE

Suitable for embedding paper tape. Combined with Certain-Teed Marco Joint Tape, the product is suitable for joint filling on plasterboard. Meets CE-marking requirements in accordance with EN 13963. Manufactured in accordance with ISO 9001 and ISO 14001. When finishing plasterboard: follow recommendations in accordance with EN 13963 or National guidelines for finishing plasterboards.

### INSTRUCTIONS

Apply by hand to clean, dry and intact surfaces. Temperature: minimum +5°C. Sand the filled surface down once it has dried. Use sandpaper with grain size 180-220. Eye and respiratory protection are recommended when sanding. Dust off before next treatment. Filled surfaces should be primed before wallpapering.

### DRYING TIME

The drying time is dependent on factors such as substrate, layer thickness, temperature and humidity.

### MATERIAL CONSUMPTION

For joint filling on plasterboard: approx. 0.3 litres/metre.  
For thin smoothing with a 1 mm layer thickness: approximately 1 litre/square metre.

### CLEANING AND DISPOSAL

Remove as much filler as possible from the tools before cleaning them in water. Filler residues must not be poured down the drain, but taken to the local waste disposal centre. Empty packaging completely and recycle it.

### STORAGE

Filler has a limited shelf life and is date-marked. Unopened packaging can be kept in a dark place, free from frost, for up to 12 months. Containers that have been opened must be sealed well.

Visit [dalapro.com](http://dalapro.com) for more information.

### TECHNICAL DATA

**Binder:** Latex co-polymer

**Solvent:** Water

**Filler:** Microspheres and white dolomite

**Particle size:** Max 0,2 mm

**pH:** Approx.9

**Colour:** Blue

**Flammability:** Does not spread or support fire

**Packaging:** 0,4-litre Tube, 3- and 10 litre plastic buckets



Dalapro Hydro 3 litre and 10 litre is packaged in a bucket manufactured mostly of recycled plastic.



This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at [www.dalapro.com](http://www.dalapro.com). Last amended 05/10/2023

Saint-Gobain Sweden AB, Scanspac  
Kemivägen 7  
SE-705 97 Glanshammar  
+46 (0)19-46 34 00  
[dalapro.com](http://dalapro.com)  
[info@dalapro.com](mailto:info@dalapro.com)